



Light rope warm white

Technical data


Light rope	Light colour	warm white	
	Colour temperature	3000 K	
	Active power	12 W/m	
	Rated voltage	24 V DC	
	Average lifetime	38000 hours	
	Protection class	IP 67	
	Ambient temperature	-20 ~ +40 °C	
	Dimensions (W x H x L)	8 x 12 x max. 5000 mm	
	Weight without cable	approx. 0,122 kg/m	
	Material	Silicone	
	Colour	white	
	Pitch dimension	50 mm	
	No. of LEDs	140 pieces/m	
Smallest bending radius	60 mm		
Dimmable	yes		
Supply cable	Length (standard)	approx. 5000 mm	
	Cross section	2 x 0,5 mm ²	
	Material	Copper / plastic	
	Weight	approx. 0,122 kg	
	Power supplies	Output / Rated power	30 W
	/ Rated voltage	24 V DC	24 V DC
	Input / Rated power	220 – 240 V AC	220 – 240 V AC
	/ Rated current	50 / 60 Hz	50 / 60 Hz
	Length	91 mm	164 mm
	Width	41 mm	61 mm
	Height	19 mm	32 mm
	Weight	0,147 kg	0,334 kg
	Material	Plastic	Plastic
	Protection class	IP 20	IP 20
	Dimmable	not dimmable	not dimmable
	For L-WW up to length	max. 2500 mm	max. 8000 mm



Light rope warm white


Installation situation

from wall to wall (cable inside the walls) *



*Example: Length between two walls = 1430 mm
 1430 - 100 = 1330 mm = Length light rope 1300 mm = 30 mm rest
 left and right 65 mm unlit – Light shines symmetrically*


from wall to wall (cable outside the walls) *



*Example: Length between two walls = 1430 mm
 1430 = Length light rope 1400 mm = 30 mm rest
 left and right 15 mm unlit – Light shines symmetrically*


* Both installation situations are also possible for the product groups **TOP-TRU...** / **TOP-WP...** / **CONCEPT-BA...** – depending on the structural situation

LAVADO




*Example: LAVADO-FLOAT L & G (standard format) = 1170 mm width washstand
 1170 - 100 mm = Length light rope 1070 mm = 20 mm rest
 left and right 60 mm unlit – Light shines symmetrically*

RELAX-NI (cable outside the niche)



Example:
 - RELAX-NI-M / -L / -XL (vertical installation) =
 internal clearance dimension 305 mm = Length light rope 300 mm
 - RELAX-NI-L (horizontal installation) =
 internal clearance dimension 457 mm = Length light rope 450 mm
 - RELAX-NI-XL (horizontal installation) =
 internal clearance dimension 68 mm = Length light rope 950 mm

RELAX-TW



*Example: Niche milling 1070 mm wide =
 Length light rope 1050 mm = 20 mm rest
 left and right 10 mm unlit – Light shines symmetrically*

The relevant recommendations and guidelines, as well as DIN regulations, European standards and safety datasheets are to be observed. The recognised architectural and technical rules apply. We accept liability for the perfect quality of our products. Our processing recommendations are based upon trials and practical experience; they can, however, be no more than general instructions without assurance as to their quality, since we have no influence on the site conditions, on the execution of the work and the processing. With the issuing of this product datasheet previous versions cease to be valid.

LUX ELEMENTS GmbH & Co. KG

An der Schusterinsel 7
 D - 51379 Leverkusen-Opladen
 Tel. +49 (0) 21 71/72 12-0
 Fax +49 (0) 21 71/72 12-40
 E-Mail info@luxelements.de

LUX ELEMENTS S.A.S

ZI-31, rue d'Ensisheim
 F - 68190 Ungersheim
 Tél. +33 (0) 3 89 83 69 79
 Fax +33 (0) 3 89 48 83 27
 E-Mail info@luxelements.fr